



404-0070-04T	
Ballast Type	Metal Halide
Lamp	70W M98 / M143
Circuit Type	HX-NPF w/o capacitor HX-HPF with capacitor
Input Frequency	60 Hz

Model No: 404-0070-04T		Capacitor (Optional)					
Input Voltage	120	208	240	277	Capacitance	8 μ F \pm 3%	
Operating Current (HPF)	0.9	0.5	0.4	0.4	Minimum Volts	280V	
Open Circuit Current	1.5	0.9	0.8	0.7	Dry	Diameter	1.20"
Starting Current (*ANSI: 0.9 ~ 1.5)	1.1	1.1	1.1	1.1		Height	2.70"
CCF (*ANSI: \leq 1.8)	1.5	1.5	1.5	1.5	Oil	Diameter	
Short Circuit Current	Secondary	1.2	1.2	1.2		1.2	Height
	Input	1.0	0.6	0.5	0.5	Case Max. Temperature	105°C Dry
Recommended Fuse (HPF)	6	3	3	2	Ignitor (Required)		
Input Voltage At Lamp Dropout					Ignitor Model	MHR1	
UL 1029 Bench Top Rise	A	A	A	A	Pulse Height (kV)	3.0 ~ 4.0	
OCV (*ANSI: \geq 235)	257 (235 ~ 330)				Pulse Width (\geq μ s)	1.3 @ 2.7	
Input Power	88W						
Power Factor	\geq 90%						
Regulation	Line Volts	\pm 5%					
	Lamp Watts	\pm 5%					
Insulation System	Class H, 180°C						
Ballast Dimension	A	1.5"					
	B	2.8"					
Ballast Net Weight	5.0 lbs.						
Leads	12"-Cross Link Polyolefin				Min. Starting Temp.	-20°F / -30°C	

* Ref. ANSI C78.43-2007

Ballast Dimension	Wiring Diagram
<p>Ballast Dimension</p> <p>3" x 4" core</p> <p>4 Holes \geq 0.195" Cleared for #10 bolts</p>	<p>Wiring Diagram</p> <p>CAP (BLK/WHT): 277V (Black), 240V (Violet), 208V (Orange), 120V (BLK/YEL)</p> <p>LAMP (Red): X3 (Blue), X1 (Red), X2 (White)</p> <p>IGNITOR</p> <p>COM White</p>
<p>Ignitor (Kit)</p> <p>2.6"</p> <p>1.4"</p>	<p>Capacitor (Kit)</p> <p>Height</p> <p>Diameter</p> <p>Dimensions are \pm 0.06". Contact Jefferson Electric for additional case dimensions</p>

When ordering, add suffix for options:

- I – with ignitor
- DC – with dry film capacitor
- OC – with oil filled capacitor
- K – with distributor replacement kit (include bracket, capacitor and ignitor as necessary.)

Specifications are subject to change without notice.

9650 S. Franklin Drive. • Franklin • Wisconsin 53132 • U.S.A • 414- 209-1620 • Fax: 414- 209-1621

• www.jeffersonelectric.com

Rev: 404-0070-04T-09-04